



INFINITY and EXPRESS Interfaces	16-Port DB9M (30030-4)	16-Port DB25M Surge (30075-5)	16-Port DB25M Surge (30035-9)	16-Port RJ45 Rackmount (30055-7)	32-Port RJ45 Rackmount (30060-1)
HARDWARE					
Number of Ports	16	16	16	16	32
Dimensions	7.5" x 0.9" x 5.5"	8.0" x 0.9" x 5.5"	7.5" x 0.9" x 5.5"	16.75" x 1.75" x 8"	16.75" x 1.75" x 8"
Surge Protection	15KV	25KV	25KV	15KV	15KV
Interfaces	RS-232/422/485	RS-232/422/485	RS-232/422/485	RS-232/422/485	RS-232/422/485
Baud Rates	300bps - 230.4Kbps	300bps - 230.4Kbps	300bps - 230.4Kbps	300bps - 230.4Kbps	300bps - 230.4Kbps
Modem Control Signals	RTS, CTS, DSR, DTR, CD, RI	RTS, CTS, DSR, DTR, CD, RI	RTS, CTS, DSR, DTR, CD, RI	RTS, CTS, DSR, DTR, CD, RI	RTS, CTS, DSR, DTR, CD, RI
ENVIRONMENTAL					
MTBF	35.1 Years	31.4 Years	31.4 Years	61.3 Years	34.2 Years
Operating Temperature	0-60° C	0-60° C	0-60° C	0-60° C	0-60° C
CERTIFICATIONS					
CE/FCC/UL/RoHS2	CE/FCC/UL/RoHS2	CE/UL/RoHS2	CE/FCC/UL/RoHS2	CE/UL/RoHS2	CE/UL/RoHS2
Warranty	5 Years	5 Years	5 Years	5 Years	5 Years