



Ethernet Device Servers	PRO 8-Port (99443-5)	Serial Hub 8-Port (99465-7)	PRO 16-Port (99451-0)	Serial Hub 16-Port (99460-2)	RTS 16 LT (99581-4)
HARDWARE					
Number of Ports: 10/100BASE-TX	2	2	2	1	2
Number of Serial Ports	8 x RS232/422/485	8 x RS232	16 x RS232/422/485	16 x RS232	16 x RS232/422/485
Serial Baud Rate	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230.4Kbps
Serial Interface	RJ45	DB9M	RJ45	DB9M	RJ45
Power Input	9-30VDC Terminal	9-30VDC Terminal	100-240VAC (US/EU Cord)	100 - 240VAC (US/EU Cord)	5-30VDC Terminal
Included Power Supply	External 90-240VAC (US/EU) input	External 90-240VAC (US/EU) input	N/A	N/A	External 100-240VAC (US/EU) input
Serial Surge Protect	25KV	15KV	25KV	15KV	15KV
ENVIRONMENTAL					
MTBF	18.2 Years	24 Years	7.3 Years	9.5 Years	TBD
Enclosure	Black Finished Steel	Black Finished Steel	Black Finished Steel	Black Finished Steel	Black Finished Steel
Dimension	10.8" x 1.8" x 6.3"	19.63" x 4" x 14"	17.25" x 1.74" x 8.0"	17.25" x 1.75" x 11"	11.5" x 1.2" x 5.4"
Operating Temperature	-37° to 74°C	-37° to 74°C	-37° to 74°C	-37° to 74°C	0° to 60°C
Installation Method	Panel Mountable	Panel Mountable	Panel/Rack Mountable	Panel/Rack Mountable	Desk/surface mount
SUPPORTED DEVICE DRIVERS					
Windows 2000/Server 2003/XP	Yes >>				
Windows Server 2008					
Windows Vista					
Windows 7					
Linux					
SOFTWARE					
TCP, UDP Socket	Yes >>				
PortVision® Remote Monitoring & Management					
Web-based Configuration					
SSL & SSH Encryption					
E-mail Event Notification					
CERTIFICATIONS					
CE/FCC/UL/RoHS2	Yes	CE/UL/RoHS2	Yes	Yes	Yes
NEMA TS2	No	Yes	Yes	No	No
Warranty	5 Years	5 Years	5 Years	5 Years	5 Years